CA12CD-S PTT ADAPTER



Meets the Needs of Mission Critical Applications

The CA12CD-S is a cordless PTT (push-to-talk) headset adapter designed to provide wireless communications and PTT functionality for applications such as Public Safety Dispatch and Air Traffic Control. The CA12CD-S is supplied with the analog Console Interface Cable (PJ-7) as shown. For digital applications, Model SSP 2468-01 (sold separately) can be installed. This USB-PTT Adapter Cable replaces the Console Interface Cable and provides a complete digital solution. The CA12CD-S uses digital processing (DECT $^{\text{TM}}$ 6.0), and operates in the UPCS band (1.92 - 1.93 GHz) in North America. European versions are also available that operate within the DECT frequency range (1.88 - 1.90 GHz). Various connector options available upon request.

APPLICATIONS:

Public Safety

Air Traffic Control

Radio Dispatch Facilities

Training/Simulation

Cordless Push-to-Talk

CA12CD-S KEY COMPONENTS

BASE UNIT:

- Two charging wells (unit supplied with an extra battery)
- Sending and receiving sensitivity controls
- Status LEDs for Power, Battery Charging and PTT
- · Coil cord (10 ft. extended) with PJ-7 connector
- Battery recharge time: 1 hour (90%);
 3 hours (100%)
- Operating temp. range: $+4^{\circ}\text{C}$ (40°F) to $+49^{\circ}\text{C}$ (110°F)

REMOTE UNIT:

- PTT button with momentary/locking selector
- On-Off button with LED
- Robust metal belt clip
- · Receiving volume control
- 12 inch cable with Quick Disconnect
- Accepts all Plantronics "H" and "HW" Tops

GLOBAL SERVICE AND SUPPORT

Backed by Plantronics industry leading global service and support.

+1-800-544-4660 (US and Canada) +1-831-458-7700 (outside US)



FEATURES	BENEFITS
PTT Switch, momentary and locking options	Field-proven reliability; user selectable
Spare Battery Pack	Two battery packs and two recharging wells: One for the remote unit and one for the spare battery — allow for 24/7 operation
Lithium-ion Batteries	Extended talk time for all day/shift use
Selectable output ranges for transmit and receive	Universal compatibility for carbon, electret, and dynamic microphone inputs
DECT 6.0 with 64-bit encryption	Secure and private communications, HIPAA compliant