



SIMPLE CONNECTIVITY. GREATER CONVENIENCE.

The Jabra GN1200 cord is the solution to a common problem of not being able to connect the headset and telephone. Even though most things have been standardised, the cord connecting the phone with the handset or headset is anything but standard as each telephone manufacturer has its own wiring code. Now, with the universal “smart” cord, Jabra GN1200, the cord will work with virtually any phone providing greater convenience.

- Works with most desk phones including IP hard phones
- Microphone amplification to boost transmit levels when connecting to low transmit volume phone systems
- Simple slide adjustment for easy setup

When hooking up a new headset there is not always a dial tone. The problem could be the headset or the telephone. But chances are it is the cord. Even though the headset and telephone may be plug-compatible, the wiring is determined by the individual telephone manufacturer.

Jabra GN1200 features eight separate wiring schemes – including three with built-in microphone amplification. Just connect the Jabra GN1200 and headset through the Quick Disconnect plug and flick the slider from one position to the next until a dial tone is heard. It’s as simple as that!

Available in both straight and coiled versions, the Jabra GN1200 fits virtually all telephones featuring a standard RJ9 modular connection.



Jabra GN1200

A BRAND BY

GN Netcom

JABRA® IS A REGISTERED TRADEMARK OF GN NETCOM A/S

WWW.JABRA.COM



Jabra GN1200

FEATURES & BENEFITS

FEATURES	BENEFITS
Simple 8-position slide adjustment	No need for a user manual; simply slide until a dial tone is heard
Standard RJ9 connector	Connects to virtually all telephones using a standard modular plug
Standard GN Quick Disconnect plug to headset	Works with any GN headset equipped with a Quick Disconnect plug
Straight 80 cm cord or 200cm lightweight coiled cord	Longer than many standard cords, yet at a competitive price
Built-in low-current microphone amplifier	Enables perfect operation with telephones that require extra signal gain such as Cisco, Panasonic, Nortel, and Avaya, plus many IP telephones

THE EIGHT SWITCH POSITIONS AND CORRESPONDING TELEPHONE SYSTEMS

JABRA GN1200 SWITCH POSITION	MATCHING TELEPHONE SYSTEM	MOD PLUG WIRING	AMPLIFIED MICROPHONE	EQUIVALENT GN CABLE
1	Standard (most common)	M-, R, R, M+	No	8800-00-01
2	Cisco IP phones 79xx series	R, M-, M+, R	No	8800-00-37
3	Ascom office and Philips phones	R, M+, M-, R	No	8800-00-03
4	Japanese phones, NEC, Nitsuko	M+, R, R, M-	No	8800-00-25
5	Plantronics Vista Base	R, R, M+, M-	No	8800-00-20
6	Panasonic phones with modular plug	M+, R, R, M-	Yes	8800-00-25A
7	Nortel digital phones and Avaya IP phones	M-, R, R, M+	Yes	8800-00-01A
8	Avaya Callmaster V and VI, Cisco IP phones 79xx series	R, M-, M+, R	Yes	8800-00-37A

ELECTRICAL SPECIFICATIONS

DC VOLTAGE	
Maximum Voltage	10v DC
Minimum Voltage	1.6v DC
Nominal Voltage	5v DC
Maximum Current	2.5 mA
Minimum Current	280 uA

CHARACTERISTICS	
AC Output Voltage	30mV (preamp on i.e. positions 6-8)
Insertion Gain	11.5dB Nom Min 10.5dB : Max 12.5dB Bias Voltage : 1.58v DC Nom , Min 1.53v DC : Max 1.76v DC (preamp output i.e. positions 6-8)
Bias Voltage	1.49v DC Nom, Min 1.38v DC : Max 1.71v DC (microphone input)