Overview

Ensure secure conversations

Keep conversations private. With up to 2x better density, this secure DECT™ wireless headset is an ideal choice for financial, medical, government, and contact centers or anywhere sensitive conversations happen.

DECT™ security

Savi 7300 headsets don't just meet security expectations, they exceed them with secure pairing, 128-bit authentication, and military-grade features, such as 256-bit AES encryption. Conversations stay private and secure.

Interference-free audio

With 2x better density than other DECT™ headsets, more people in shared spaces benefit from wireless headsets with clear, interference-free audio. IT can deploy more Savi 7300 Office Series compared to other DECT™ headsets without concern.

Work where you want

With a discreet, easy-to-use DECT wireless adapter, the Savi 7300 UC series is ready to work where you do. Simply plug the adapter into your PC and you are ready to collaborate — in the office, remote, or on the go.

Features

Keep conversations private

Make sure nearby conversations are not overheard. The noise-canceling microphone enhanced with Poly Acoustic Fence technology ensure private conversations stay private.

DECT™ security standards

Designed to meet the highest-level DECT™ Security Step C enhanced with military-grade FIPS 140-2 listed features, such as 256-bit AES encryption. [2]

Meet enterprise security needs

Ideal for use in financial, medical, and government environments, where Bluetooth® technology is typically banned.

Remote management

Stay in control with remote device management for settings, firmware, and security updates.

Roaming range

Give users more freedom to move with a line-of-sight wireless range of up to 450 ft / 137 m.

Training made easy

Make training and collaboration easy with the ability to conference up to 4 headsets on the D400 dongle.

[2] DECT security standards can be found on https://etsi.org.

Specifications

Audio	Microsoft Teams Open Office certified; Microphone noise cancellation with Acoustic Fence technology
Weight	120 g
Weight	0.26 lb
Package dimensions (W x D x H)	185 x 210 x 115 mm
Package weight	300 g
Battery life	Up to 13 hours (talk time); Up to 52 hours (standby time)
UPC number	197497838046
Manufacturer Warranty	Poly standard two-year limited warranty
What's in the box	Quick start guide; Wireless headset; Office base; Telephone cable; Micro USB to Type-C® cable; USB Type-C® to USB Type-A cable

Additional specifications

Acoustic protection technology	SoundGuard Digital ^[1,2]
Battery type	Rechargeable Li-ion polymer
Button user controls	Call answer/end; Mute; Volume +/-; Power on/off
Cartons per layer	10
Cartons per pallet	80
Charge time	<2 hours
Color	Black
Compatibility	Compatible with PCs via DECT $^{\text{\tiny{M}}}$, USB Type-A D400 adapter or USB Type-A/C $^{\odot}$ adapter
Compatible Operating Systems	Windows 11; Windows 10; macOS
Connection type	Wireless: DECT™, USB Type-A D400, USB Type-A/C® adapter
Datasheet photo 1	AHID/f1e50038f4c848a26405694db09d7a5cbf181af5
ECCN	5A992
Ear cushions	Artificial leather (surface material)
Ecolabels	TCO Certified
HTS code	8517620090
Indicator light	On call
Management Software	Poly Lens ^[3]
Master carton dimension (imperial)	6.1 x 23.42 x 8.85 in
Master carton dimension (metric)	15.5 x 59.5 x 22.5 cm
Master carton weight (imperial)	8.68 lb
Master carton weight (metric)	3.94 kg
Microphone bandwidth	100 Hz to 10 kHz
Microphone type	Noise cancelling
Multiple order quantity	5
Package dimensions (W \times D \times H)	7.48 x 8.26 x 2.16 in
Package weight	0.66 lb
Pallet (layers)	8
Pallet dimensions	40 x 48 x 58.66 in
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	787.05 lb
Pallet weight	357 kg
Products per pallet	400

Products per pallet layer	50
Speaker bandwidth	20 Hz to 20 kHZ (multimedia mode); 100 Hz to 6.8 kHZ (wideband mode)
UNSPSC code	43191638
Voice alerts	Volume maximum; Volume minimum; Mute on; Mute off; Muted; Connection status; Talk time; Battery low
Wireless range	Up to 137 m in open area; Up to 40 m in typical office environment
Wireless range (imperial)	Up to 450 ft in open area; Up to 130 ft in typical office environment

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

- [2] Requires Poly Lens Desktop App to enable SoundGuard Digital features.
- [3] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Services

Communication & Collaboration

★: Recommended

Poly Support Services

3 year Poly+ Savi Service	PSAVI312 ★
3 year Partner Poly+ Savi Service	PSAVI362

Hybrid Work Solutions

Audio ★: Recommended

Audio Accessories

Dala ADA 24 (ALCATEL) Electronic Harley italy TAA	9505344
Poly APA-24 (ALCATEL) Electronic Hookswitch TAA	85Q52AA
Poly APC-43 Electronic Hookswitch TAA	85Q55AA
Poly APD-80 Electronic Hookswitch TAA	85Q58AA
Poly APN-91 Electronic Hookswitch TAA	85Q59AA
Poly APP-51 Electronic Hookswitch TAA	85Q60AA
Poly APS-11 Electronic Hookswitch TAA	85Q78AA
Poly APU-76 Electronic Hookswitch TAA	85R00AA
Poly APV-63 Electronic Hookswitch TAA	85R01AA
Poly Busy Light (Angle Plug)	920Q4AA
Poly EHS 3.5mm to 3.5mm Cable	85R17AA
Poly HL10 Handset Lifter	784Q1AA
Poly HL10 Handset Lifter TAA	8R713AA
Poly HL10 Handset Lifter with Straight Plug TAA	784Q2AA
Poly HL10 Lifter Arm +Ring Detector Accessory	8A7E3AA
Poly RD-1 Electronic Hookswitch	85R71AA
Poly Savi 7300 Battery with Removal Tool	784P8AA
Poly Savi 7300 Leatherette Ear Cushions (2 Pieces)	783Q8AA
Poly Savi 7310 Monaural DECT 1880-1900 MHz Top	8Y9B6AA
Poly Savi 7310 Monaural DECT 1920-1930 MHz Top	783N0AA
Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1880-1900 MHz Top	8Y9B8AA
Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1893-1906 MHz Top	9V8Z7AA
Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1920-1930 MHz Top	783N2AA
Poly Savi 7320 Stereo DECT 1880-1900 MHz Top	8Y9B7AA
Poly Savi 7320 Stereo DECT 1893-1906 MHz Top	9V8Z6AA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Top	783N1AA
Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1880-1900 MHz Top	8Y9B9AA
Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1893-1906 MHz Top	9V8Z8AA
Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1920-1930 MHz Top	783N3AA
Poly Savi 7410/7420 Office Charging Cradle	8L556AA
Poly Savi 8400/7400 Office DECT 1920-1930 MHz Base	8L571AA

Poly Savi 8400/7400 Office Microsoft Teams Certified DECT 1920-1930 MHz Base	8L562AA
Poly Savi 8410/8420 Office Charging Cradle	8L573AA
Poly Savi 8440/8445 Office Charging Cradle	8L577AA
Poly Savi D400 DECT 1920-1930 MHz Dongle	8L550AA
Poly Savi D400 Microsoft Teams Certified DECT 1920-1930 MHz Dongle	8L552AA
Poly Savi D400 UC DECT 1920-1930 MHz Dongle	85T33AA
Poly Savi D400 UC Microsoft Teams Certified DECT 1920-1930 MHz Dongle	85T34AA
Poly Savi Office Power Supply with Right Angled Plug -9V 1000mA	8L5A2AA
Poly Savi Office S2 Telephone Cable	85R55AA
Poly Savi Office Straight Plug Online Indicator	85R52AA
Poly Savi Office Telephone Interface Cable	85R57AA
Poly Savi Office Universal AC Power Supply with Straight Plug -9V 1000mA	85R59AA
Poly USB-A to USB-C Adapter	85Q48AA
Poly USB-C to USB-A Adapter	85Q49AA
Poly Voyager USB-A Charging Stand	783R6AA
Poly Voyager USB-C Charging Stand	783R7AA

Disclaimer — Copyright

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (us-en) – Jul 23, 2025 8:53 PM UTC+0000