hp

Poly Savi 7320 UC Stereo DECT 1920-1930 MHz Headset (8L549AA)

Overview

Ensure secure conversations

Keep conversations private. With up to 2x better density, this secure DECT[™] wireless headset is an ideal choice for financial, medical, government, and contact centers or anywhere sensitive conversations happen.

DECT™ security

Savi 7300 headsets don't just meet security expectations, they exceed them with secure pairing, 128-bit authentication, and militarygrade features, such as 256-bit AES encryption. Conversations stay private and secure.

Work where you want

With a discreet, easy-to-use DECT wireless adapter, the Savi 7300 UC series is ready to work where you do. Simply plug the adapter into your PC and you are ready to collaborate — in the office, remote, or on the go.

Interference-free audio

With 2x better density than other DECT[™] headsets, more people in shared spaces benefit from wireless headsets with clear, interference-free audio. IT can deploy more Savi 7300 Office Series compared to other DECT[™] headsets without concern.

Keep conversations private

Make sure nearby conversations are not overheard. The noise-canceling microphone enhanced with Poly Acoustic Fence technology ensure private conversations stay private.

DECT[™] security standards

Designed to meet the highest-level DECT[™] Security Step C enhanced with military-grade FIPS 140-2 listed features, such as 256-bit AES encryption.^[2]

Meet enterprise security needs

Ideal for use in financial, medical, and government environments, where Bluetooth[®] technology is typically banned.

Remote management

Stay in control with remote device management for settings, firmware, and security updates.

Roaming range

Training made easy

Give users more freedom to move with a line-of-sight wireless range of up to 450 ft / 137 m.

Make training and collaboration easy with the ability to conference up to 4 headsets on the D400 dongle.

[2] DECT security standards can be found on https://etsi.org.

Specifications

| Audio | Microsoft Teams Open Office certified; Microphone noise cancellation with Acoustic Fence technology |
|--------------------------------|---|
| Weight | 160 g |
| Weight | 0.35 lb |
| Package dimensions (W x D x H) | 185 x 210 x 115 mm |
| Package weight | 300 g |
| Battery life | Up to 13 hours (talk time); Up to 52 hours (standby time) |
| UPC number | 197497837766 |
| Manufacturer Warranty | Poly standard two-year limited warranty |
| What's in the box | Quick start guide; Wireless headset; Office base; Telephone cable; Micro USB to Type-A cable; Micro USB to Type-C® cable; USB Type-C® to USB Type-A cable |

Additional specifications

| Acoustic protection technology | SoundGuard Digital ^[1,2] |
|---------------------------------------|---|
| Battery type | Rechargeable Li-ion polymer |
| Button user controls | Call answer/end; Mute; Volume +/-; Power on/off |
| Cartons per layer | 10 |
| Cartons per pallet | 80 |
| Charge time | <2 hours |
| Color | Black |
| Compatibility | Compatible with PCs via DECT™, USB Type-A D400 adapter or USB Type- A/C® adapter |
| Compatible Operating Systems | Windows 11; Windows 10; macOS |
| Connection type | Wireless: DECT™, USB Type-A D400, USB Type-A/C [®] adapter |
| Datasheet photo 1 | AHID/9a43e17ba098708d67f080a781a23fe5bbc551c6 |
| ECCN | 5A992 |
| Ear cushions | Artificial leather (surface material) |
| Ecolabels | TCO Certified |
| HTS code | 8517620090 |
| Indicator light | On call |
| Management Software | Poly Lens ^[3] |
| Master carton dimension (imperial) | 6.1 x 23.42 x 8.85 in |
| Master carton dimension (metric) | 15.5 x 59.5 x 22.5 cm |
| Master carton weight (imperial) | 9.12 lb |
| Master carton weight (metric) | 4.14 kg |
| Microphone bandwidth | 100 Hz to 10 kHz |
| Microphone type | Noise cancelling |
| Multiple order quantity | 5 |
| Package dimensions (W x D x H) | 7.48 x 8.26 x 2.16 in |
| Package weight | 0.66 lb |
| Pallet (layers) | 8 |
| Pallet dimensions | 40 x 48 x 58.66 in |
| Pallet dimensions (W x D x H) | 101.6 x 121.9 x 149 cm |
| Pallet weight | 787.05 lb |
| Pallet weight | 357 kg |
| Products per pallet | 400 |

| Products per pallet layer | 50 |
|---------------------------|---|
| Speaker bandwidth | 20 Hz to 20 kHZ (multimedia mode); 100 Hz to 6.8 kHZ (wideband mode) |
| UNSPSC code | 43191638 |
| Voice alerts | Volume maximum; Volume minimum; Mute on; Mute off; Muted; Connection status; Talk time; Battery low |
| Wireless range | Up to 137 m in open area; Up to 40 m in typical office environment |
| Wireless range (imperial) | Up to 450 ft in open area; Up to 130 ft in typical office environment |

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

[2] Requires Poly Lens Desktop App to enable SoundGuard Digital features.

[3] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Services

Communication & Collaboration

Poly Support Services

3 year Poly+ Savi Service

3 year Partner Poly+ Savi Service

\star : Recommended

 $\text{PSAVI312} \star$

PSAVI362

Hybrid Work Solutions

Audio

Audio Accessories

Poly APA-24 (ALCATEL) Electronic Hookswitch TAA 85Q52AA Poly APC-43 Electronic Hookswitch TAA 85Q55AA Poly APD-80 Electronic Hookswitch TAA 85Q58AA Poly APN-91 Electronic Hookswitch TAA 85Q59AA Poly APP-51 Electronic Hookswitch TAA 85Q60AA Poly APS-11 Electronic Hookswitch TAA 85Q78AA Poly APU-76 Electronic Hookswitch TAA 85R00AA Poly APV-63 Electronic Hookswitch TAA 85R01AA Poly Busy Light (Angle Plug) 920Q4AA Poly EHS 3.5mm to 3.5mm Cable 85R17AA Poly HL10 Handset Lifter 784Q1AA Poly HL10 Handset Lifter TAA 8R713AA Poly HL10 Handset Lifter with Straight Plug TAA 784Q2AA Poly HL10 Lifter Arm + Ring Detector Accessory **8A7E3AA** Poly RD-1 Electronic Hookswitch 85R71AA Poly Savi 7300 Battery with Removal Tool 784P8AA Poly Savi 7300 Leatherette Ear Cushions (2 Pieces) 783Q8AA Poly Savi 7310 Monaural DECT 1880-1900 MHz Top 8Y9B6AA Poly Savi 7310 Monaural DECT 1920-1930 MHz Top 783N0AA Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1880-1900 MHz Top 8Y9B8AA Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1893-1906 MHz Top 9V8Z7AA Poly Savi 7310 Monaural Microsoft Teams Certified DECT 1920-1930 MHz Top 783N2AA Poly Savi 7320 Stereo DECT 1880-1900 MHz Top 8Y9B7AA Poly Savi 7320 Stereo DECT 1893-1906 MHz Top 9V8Z6AA Poly Savi 7320 Stereo DECT 1920-1930 MHz Top 783N1AA Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1880-1900 MHz Top 8Y9B9AA Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1893-1906 MHz Top 9V8Z8AA Poly Savi 7320 Stereo Microsoft Teams Certified DECT 1920-1930 MHz Top 783N3AA Poly Savi 7410/7420 Office Charging Cradle 8L556AA Poly Savi 8400/7400 Office DECT 1920-1930 MHz Base 8L571AA

 \star : Recommended

| Poly Savi 8400/7400 Office Microsoft Teams Certified DECT 1920-1930 MHz Base | 8L562AA |
|---|---------|
| Poly Savi 8410/8420 Office Charging Cradle | 8L573AA |
| Poly Savi 8440/8445 Office Charging Cradle | 8L577AA |
| Poly Savi D400 DECT 1920-1930 MHz Dongle | 8L550AA |
| Poly Savi D400 Microsoft Teams Certified DECT 1920-1930 MHz Dongle | 8L552AA |
| Poly Savi D400 UC DECT 1920-1930 MHz Dongle | 85T33AA |
| Poly Savi D400 UC Microsoft Teams Certified DECT 1920-1930 MHz Dongle | 85T34AA |
| Poly Savi Office Power Supply with Right Angled Plug -9V 1000mA | 8L5A2AA |
| Poly Savi Office S2 Telephone Cable | 85R55AA |
| Poly Savi Office Straight Plug Online Indicator | 85R52AA |
| Poly Savi Office Telephone Interface Cable | 85R57AA |
| Poly Savi Office Universal AC Power Supply with Straight Plug -9V 1000mA | 85R59AA |
| Poly USB-A to USB-C Adapter | 85Q48AA |
| Poly USB-C to USB-A Adapter | 85Q49AA |
| Poly Voyager USB-A Charging Stand | 783R6AA |
| Poly Voyager USB-C Charging Stand | 783R7AA |
| | |

Disclaimer — Copyright

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (us-en) – Jul 23, 2025 8:58 PM UTC+0000