




ICON
BY JPL

JPL-Icon 100-PM

Simple, sturdy, no fuss design



QD headsets are supplied with a top cable only.
All QD headsets require an additional bottom lead.
Please check the compatibility tool on
www.jpltele.com for the correct bottom lead
for your phone or PC.



Overview

Features	Single speaker professional headset with left / right ear side boom wearing compatible
	Surround Shield™ noise cancelling microphone - effectively blocks out all background noise even in the noisiest office
	Wideband enabled speakers with Sound Shield™ acoustic shock protection
	'Put and stay' ratchet microphone boom arm
	Overhead, sure-fit fully adjustable headband
	Fitted with gimbal action 72mm x 66mm on-ear soft leatherette ear cushions for maximum all day comfort
What's included	Binaural headset with PLX QD connector, and Quick Start Guide
Headset Weight	Mid-weight Headset, ~ 78g
Connection	PLX fitted as standard or GN** compatible QD options
Compatibility	For full range of bottom leads* and compatibility information - Go to Jpltele.com
Certifications	UKCA, CE, FCC, RoHS, REACH
Warranty	2 years standard no quibble repair or replace warranty
MOQ	Master Shipping Carton: 80
EAN:	5060969681257
SKU:	575-438-001
Country of Origin:	Manufactured in South Korea - TAA approved
PLX = Plantronics compatible QD	

* optional to purchase seperately.

** GN QD available on special request

Technical Data

Microphone:

Impedance:	2.2kΩ (F=1 KHz)
Sensitivity:	-44dB ± 3dB
Directivity:	Noise Cancellation Microphone
Frequency Range:	100Hz to 8kHz
Distortion:	Less than 10%
Operational Voltage:	1.0 V ~ 10 V
S/N Ratio:	More than 55dB

Speaker:

Diameter:	36 mm Wideband
Impedance:	150Ω ± 15% at 1kHz
Sensitivity:	88dB ± 2dB (0.1W/0.1m)
Max Input Power:	100 mV
Frequency Response:	100Hz to 20KHz
Distortion:	Less 10% at 1kHz 100mV
Operating Temp:	0°C to 40°C
Storage Temp:	-10°C to 60°C