




Available Q4 2026

JPL-Agent 50

Left and right side wearing noise cancelling ear hook headset



Overview

| | |
|--|---|
| Features | <p>Left and right side wearing noise cancelling ear hook headset</p> <p>Surround Shield™ Electret condenser noise cancelling microphone - effectively blocks out all background noise even in the noisiest office</p> <p>Easy position microphone boom arm</p> <p>Small, medium and large sized gel ear cushions supplied</p> <p>QD wired</p> |
| What's included | Monaural ear hook headset with PLX QD connector, clothing clip, gel ear cushion, soft rubber ear hook sleeve and Quick Start Guide |
| Headset Weight | Light-weight ear hook headset |
| Connection | PLX QD fitted as standard or GN** compatible QD options |
| Compatibility | For full range of bottom leads* and compatibility information - Go to Jpltele.com |
| Certifications | UKCA, CE, FCC, RoHS, REACH |
| Warranty | 2 years standard no quibble repair or replace warranty |
| MOQ | Master Shipping Carton: 60 |
| EAN: | 5060969684012 |
| SKU: | 575-478-001 |
| Country of Origin: | Manufactured in South Korea - TAA approved |
| PLX = Plantronics compatible QD ** GN QD available on special request | |

QD headsets are supplied with a top cable only. All QD headsets require an additional bottom lead. Please check the compatibility tool on www.jpltele.com for the correct bottom lead for your phone or PC.

Technical Data

| | |
|---------------------|-------------------------------|
| Microphone: | Electret Condenser |
| Directivity: | Noise Cancellation Microphone |
| Speaker Diameter: | 13 mm |
| Frequency Response: | 20Hz to 20KHz |
| Sensitivity: | -47dB ± 3dB |
| Impedance: | 32Ω |
| Max Input Power: | 100 mW |
| Operating Temp: | 0°C to 40°C |
| Storage Temp: | -10°C to 60°C |



Designed in the UK, Manufactured in South Korea